



## Lubricants – Greases

Version: 626/01

# Valvoline™ Marine Calcium 2

*High performance and very adhesive lubricating grease that resists water washing and prevents rust and corrosion. The product has good wear-resisting properties and contains titanium.*

Valvoline Marine Calcium 2 is an Anhydrous Calcium thickened lubricating grease formulated with high viscosity mineral base oil and enhanced with titanium. The product has excellent load carrying capacity, premium corrosion preventive properties and superior stay-in-place characteristics, which is essential for the complete protection of marine equipment.

### Performance levels

DIN 51502:	KP2G-15
ISO 6743:	L-XBBHB 2

### Applications

Especially suitable for use in marine and in heavy load applications that require extra adhesiveness and excellent water resistance.

Bearings in wet conditions.

### Features & Benefits

#### Superior protection

Valvoline Marine Calcium 2 protects against rust and corrosion and has premium oxidation stability properties. The grease has a good mechanical stability and excellent water resistance so that it will stay in place, even in high pressure marine applications.

#### Superior performance

The product lubricates and protects under the most severe circumstances like damp and wet conditions. In the presence of water, a good lubricating film will be maintained.

#### Multipurpose applications

Valvoline Marine Calcium 2 was developed for a wide range of temperatures and high speeds in marine applications. The product can resist higher temperatures than conventional Calcium 2 greases.

#### Severe working conditions

The product can even be used in unfavorable working conditions like mining.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineeurope.com](http://www.valvolineeurope.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Marine Calcium 2	
NLGI grade	2
Thickener	Calcium anhydrous
Colour	White
Texture	Smooth, Tacky, Very adhesive
Density @ 20 °C	0,92
Application temperature °C	-15 to +100
Oil Viscosity, mm <sup>2</sup> /s @ 40°C	460
Dropping Point, °C	145
4-Ball Weld Load, kg	200
Water wash out @ 80°C	2%
Copper Corrosion	1b
Wheel bearing test, %	2

**This information only applies to products manufactured in the following location(s): Europe**

™ Trademark of Valvoline, registered in various countries © 2017

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

## Protect the environment

Take used oil and grease to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –